

#### **Product**

# Condensate Pumps PROCP-22S Series Condensate Pumps

#### **Application**

Condensate removal for HVAC/R equipment

# Purpose

This product Is designed to automatically evacuate condensate or water discharge from HVACR equipment up to 22' vertically once the condensate in the reservoir reaches a specified level.

# Advantages

Asurity® PROCP-22S series pumps beat the industry standard of 20' lift height by 2 feet and come with innovative features such as: vibration dampening motor mounts, metal mounting tabs, four inlet holes (and 3 poly covers for the unused), built in safety overflow switch for added protection and detailed installation instructions. PROCP-22S is also available with 20' of 3/8" tubing as well.





# **Maximum Condensate Temperatures**

- Continuous duty 140°F
- Maximum inlet temperature 160°F
- Not suitable for contact with steam or gases that exceed 160°F

#### Rated Voltage

120VAC / 230VAC / 60hHz

#### **Rated Current Draw**

- 1.9 Amps (120VAC)
- 1.0 Amps (230VAC)

# Input Type

- USA 3-prong molded plug (120VAC)
- NEMA 6-15 (230VAC)

#### Maximum Lift Height

PROCP-22S Series: 22'

# Flow Rate @ Zero Head

PROCP-22S: 1.6 gallons per minute

#### **Dimensions**

- PROCP-22S: 11.8" x 5.9" x 6.7"
- PROCP-22S: 5 lbs.

# Inlet Height from Base

PROCP-22S: 4.4"

#### **Tank Capacity**

• PROCP-22S: 1/2 gallon

#### **Included Accessories**

- Instruction Booklet
- Metal Hang Tabs
- Polyethylene inlet covers (3)
- 5" Remote Shutoff Leads

Every Asurity® condensate pump is computer tested to ensure excellent performance at all pumping levels.



# Wiring Color References

# 120V

- Black Live/Hot
- White Neutral
- Green Ground
- (All installations must conform to local building codes)

#### 230V

- Brown Live/Hot
- Blue Live/Hot
- Green/Yellow Ground
- (All installations must conform to local building codes)

# SKU Specific Package Metrics

CATALOG NO.	VOLTS	LIFT	UPC	POWER CORD	ORDER MULTIPLE
PROCP-22S	120V	22'	095247173020	6'	6
PROCP-22ST	120V w/ tubing	22'	095247173068	6'	6
PROCP-22S-230	230V	22′	095247173044	6'	6
PROCP-22ST-230	230V w/ tubing	22'	095247173082	6'	6

# PROCP-22S Pump Performance Curve

